

NuPower II

NUPOWER® II is a multi-functional drywash compound specially formulated to: clean, deoxidize, protect and preserve aircraft exterior paint. **NUPOWER**® II removes all types of soil conditions including: surface dirt, carbon, lubricants, hydraulic fluids etc. while providing a smooth and glossy surface. **NUPOWER**® II provides a surface barrier which seals the substrate against soil re-deposition and protects against UV deterioration.

Nuvite CHEMICAL COMPOUNDS

APPLICATION

Apply **NUPOWER**® **II** by hand, spray or mop head. Agitate area evenly while material is still wet. Allow to fully dry, approximately 5-10 minutes. Buff with a clean mop head or dry soft terry cloth to shine.

For heavily soiled surfaces, wipe or wet wash with **CitriCut**® or **SS9-3** prior to using **NUPOWER**® II.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Effective soil removal
- Removes surface oxidation from paint and metal surfaces
- Preserves and protects against further oxidation, UV and atmospheric corrosion
- Safe to all aircraft components; conforms to airframe OEM standards and specifications
- Conforms to: BOEING: BSS7432, D6-17487; DOUGLAS: CSD-1; AIRBUS: AIMS 09-00-002; AMS: AMS1476, AMS1526C, AMS1527B, AMS1533A, AMS1650C

PHYSICAL CHARACTERISTICS

Test	NuPower II
Appearance	Tan Semi-Viscous Liquid
рН	11.5 - 11.8
Specific Gravity	0.940

AVAILABILITY

55 Gallon(s), 5 Gallon(s), 1 Gallon(s), 1 Quart(s), 1 Pint(s), 4 Ounce, 1 Ounce

The Science of Surfacing* | 85 Jetson Lane | Central Islip, NY 11722 | 516.935.4000 | Universalphotonics.com