

NuGear SC

NUGEAR SC is a heavy duty aqueous cleaning compound for exterior aircraft engine and component degreasing applications. **NUGEAR SC** is used as a wet wash or in a hot immersion tank and spray cabinet application. According to soil conditions, NUGEAR can be used in concentrate or dilution.



APPLICATION

Normal - Hand Cleaning: Use full strength or dilute 1:4 - 1:10 with water. Apply to surface by mop or spray method. Agitate to loosen soil followed by water rinse and dry with terry towel.

General Component Part Cleaning: Dilute according to soil condition and immerse in tank or basket under ambient or hot temperature method or in ultrasonic equipment.

Engine Component Cleaning - Hot immersion tank: Dilute **NUGEAR SC** 1:4 for use in tank applications at 140°F (60°C). Follow OEM manufacturer's Maintenance Manual procedures and requirements.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Superior wetting and soil penetration
- Conforms to Airframe OEM standards and specifications
- Rolls Royce, General Electric, and Pratt & Whitney SPMC 151, PMC 5404, and PMC 1481 approved

PHYSICAL CHARACTERISTICS

Test	NuGear SC
Appearance	Yellow Liquid
рН	11.8 - 12.5
Specific Gravity	1.01
Solubility in water	Infinite

AVAILABILITY

55 Gallon(s), 5 Gallon(s), 1 Gallon(s), 1 Quart(s)

The Science of Surfacing* | 85 Jetson Lane | Central Islip, NY 11722 | 516.935.4000 | Universalphotonics.com